





1. CLEAR APERTURE: $>80\%$ WxL
2. DIAMETER TOLERANCE: $+0.0/-0.1$ mm
3. EXTINCTION RATIO($T_p:T_s$): $>2000:1$
4. DESIGN WAVELENGTH: 355 nm
5. TRANSMITTED BEAM DEVIATION: ≤ 5 arcmin
6. REFLECTED BEAM DEVIATION: $\leq 90^\circ \pm 5$ arcmin
7. SURFACE QUALITY(S/D): 40/20
8. WAVEFRONT ERROR(RMS): $< \lambda/4@633$ nm
9. PARALLELISM(S1,S2,S3,S4): ≤ 10 arcsec
10. AR COATING(S1,S2,S3,S4): V Coating @355 nm, $R_{abs} < 0.25\%$, 0° AOI
11. S POLARIZATION REFLECTION: $>99.5\%$
12. P POLARIZATION TRANSMISSION: $>95\%$
13. CHAMFER: <0.5 mm $\times 45^\circ$
14. OPERATING TEMPERATURE: $-50^\circ \sim 90^\circ$
15. GLUED(S5,S6): LIGHT GLUE PROCESS

DRAWING PROJECTION					PBS25—355HP					
	NAME	DATE								
DRAWN	NIC	21/October/2025	POLARIZATION BEAM SPLITTER			MATERIAL	WEIGHT	SCALE	REV	
APPROVAL	DICK	21/October/2025				FOLLOW THE PARTS	0.000	10:1		
THE DRAWINGS ARE ONLY FOR TYPE SELECTION INFORMATION			shop.zolix.com.cn							